

## TRANSCOL ADERE-P

*Adhesion primer used as a joining bridge in cementitious bases*

**COLOUR**  
Yellowish

**PACKING**  
20kg bucket

**USE**  
Exterior/Interior

**THEORETICAL  
CONSUMPTION**  
1 L / 5 to 6 m<sup>2</sup>

### 1. PURPOSE

Yellowish aqueous dispersion works as a bonding primer between support and applied glue or mortar. Formulated on the basis of acrylic ester in aqueous dispersion, it also prolongs the durability of the substrate/coating cohesion.

### 2. TECHNICAL DATA

Property	Value
<b>Look</b>	Yellowish aqueous dispersion
<b>Density</b>	1.0 to 20°C (DIN 53217)
<b>PH</b>	4.0 to 4.5 to 20°C (DIN 53785)
<b>Viscosity</b>	10 to 11 seconds at 20°C (Flow viscometer 4, DIN 53211)
<b>Drying time</b>	24 to 48 hours

*Laboratory results according to appropriate test standards under controlled conditions*

### 3. COMPOSITION

Acrylic ester in aqueous dispersion.

### 4. SUPPORT

It can be used on supports in critical condition and of different natures. Applied to concrete. The substrates must be free of dust, formwork, disaggregated or unstable materials, efflorescence or any other type of impurities that may alter the good consistency of the substrate, as well as fungi or other stains. Cracks must be eliminated beforehand.

### 5. PREPARATION

Product ready to apply.

Homogenize before applying, without adding water, cementitious mortars or other additives.

### 6. APPLICATION

Apply the product with a roller or a brush in a large and uniform way (preferably equipped with a long handle), in order to ensure an even distribution. Stir the solution periodically. After application, wait 1 hour before applying a glue or mortar.

## 7. SAFETY

It is recommended to use a dust mask to protect the respirable crystalline silica, goggles and gloves when handling the product. If there is contact with eyes, rinse thoroughly with clean water. Do not ingest. Refer to the Product Safety Data Sheet.

## 8. USEFUL ADVICE

- ◆ Application temperature from 5°C to 30°C;
- ◆ Excess water in the preparation alters the physical characteristics of the product;
- ◆ Never add any other type of product to the mortar;
- ◆ Never use acid or excess water to clean mortar residues;
- ◆ Do not apply in rain, very humid environment or strong wind;
- ◆ Do not apply on icy surfaces or at risk of frost within 24 hours of applying the product;
- ◆ Protect from direct sun rays and any heat source.

## 9. STORAGE

Store in a dry and ventilated place, on the pallet and in the original closed and protected packages, for 180 days from the date of manufacture.